



Art. 62054

## Engine Flush



**Reaction time**  
approx. 15 - 20 minutes



**Application field**  
all petrol and diesel engines



**Consumption**  
300 ml for 5 l oil // 60 ml for 1 l



**Application interval**  
with every oil change

- Application**
- 1) Add to the oil system before every oil change.
  - 2) Let the engine idle for approx. 15-20 minutes.
  - 3) Carry out the oil change according to the manufacturer's instructions.

**Description** GAT Engine Flush is suitable for use in all diesel and petrol engines with or without turbocharger. Neutralizes aggressive residues from the combustion process. Reliably dissolves operationally caused contamination and resin formations in the complete oil system which can then easily be removed with the used oil during the oil change. GAT Engine Flush contains powerful anti-friction lubricants that reliably protect the engine during the cleaning process.

**Benefits** Only a clean engine can run on full power! Easy to use – no extra effort. Removes lastingly deposits and residues in the upper cylinder area e.g. from piston rings, annular gaps, hydraulic valve lifter and valve train. The results are a considerably improved and stable compression in all cylinders. Fuel and oil consumption as well as wear and tear are reduced. Less harmful exhaust emissions support the environment and extend the life span of the catalytic converter. Avoids recontamination of the fresh oil with residues and deposits of the used oil.

**PU** 24 x 300 ml

**Packing sizes** 300 ml // other sizes available on request

Although our information is based on intense product tests and studying and therefore considered as reliable, it nevertheless has solely advisory character.