



Art. 62010

DPF Cleaning Liquid



Reaction time
approx. 8 to 10 hours



Application field
all diesel particulate filters



Consumption
depending on filter size



Application interval
on demand

- Application**
- 1) Demount the particulate filter and fill in the cleaning liquid - approx. 3 to 5 litres depending on the filter size.
 - 2) Let the product take effect for approx. 8 to 10 hours.
 - 3) Check filling level regularly and refill if necessary.
 - 4) Empty particulate filter.
 - 5) Thoroughly rinse the filter with clear water after the cleaning process.
 - 6) Reassemble the diesel particulate filter and do a test drive for at least 15 min.
- Application ratio 1:4 with water (1 L sufficient for 4 L cleaning liquid), in case of strong contamination use 1:1 ratio. Suitable for all diesel particulate filters.
- Description** GAT DPF Cleaning Liquid is a highly efficient additive combination for cleaning of dismantled diesel particulate filters. Dissolves contamination in the diesel particulate filter and regenerates its full functionality.
- Benefits** Cleans the diesel particulate filter. Dissolves all operationally caused residues and contamination. Readily biodegradable. Provides a clear cost benefit compared to installation of a new diesel particulate filter.
- PU** 12 x 1000 ml
- Packing sizes** 1000 ml // other sizes available on request

Although our information is based on intense product tests and studying and therefore considered as reliable, it nevertheless has solely advisory character.