



Art. 62034

Air Intake Cleaner Diesel



Reaction time
approx. 30 minutes



Application field
all petrol engines



Consumption
300 ml for 1 application



Application interval
every 6 months /// on demand

Application GAT Air Intake Cleaner is exclusively developed for application with the „GAT Stream“ device and suitable adapters.

Check the engine oil level before application. If the engine oil is contaminated with diesel fuel, an oil change has to be carried out before cleaning of the diesel particulate filter can be done.

- 1) spray approx. 150 ml evenly in all intake ducts by moving the adapter back and forth.
- 2) Let the product take effect for approx. 30 mins, then start the engine.
- 3) Let the engine run at 2500 rpm.
- 4) Spray the remaining product intermittently into air intake system.
- 5) Finally check the valve clearance.

Description For the cleaning of the entire air intake system. Removes deposits in the air intake system, combustion chamber, throttle valves, inlet and outlet valves and valve seats. Especially recommended for insufficient throttle response and compression as well as engine knocking and dieseling.

Benefits Only a clean fuel system guarantees clean and powerful combustion and efficient engine performance! Reduces the fuel consumption and the exhaust gas emission values. Ensures a smooth idling.

PU 24 x 300 ml

Packing sizes 300 ml // other sizes available on request